



科海光器件

ST PATCH-CORD



APPLICATIONS

-Local Area Networks (LANs)
-Instrument

-Data processing networks
-Premise installations

FEATURES

-Low insertion loss and back reflection loss
-Good Durability
-Standard: Telcordia GR-326-CORE

-Good exchangeability
-High temperature stability

AVAILABILITY

-Simplex/Duplex patch-cord available
-Pigtail available

-Fan-out available
-Various boot (cable) sizes available

SPECIFICATIONS

	Single mode	Multimode
Insertion Loss	≤0.20dB	≤0.25dB
Return Loss	≥50 dB	
Repeatability	≤0.1	
Durability	≤0.2 dB typical change, 1000 matings	
Interchangeability	≤0.2dB	
Tensile strength	>10kg	
Operating Temperature	-40 to + 85°C	-40 to + 85°C

ORDERING OPTIONS

Boot (cable) Size	Boot Color	Fiber Type	Cable number	Length
0.9mm	Black	9/125μm (SM)	Simplex	Customized
2.0mm	Red	50/125μm (MM)	Duplex	
3.0mm	Brown	62.5/125μm (MM)	Fan-out (4f)	
			Fan-out (6f)	
			Fan-out (8f)	
			Fan-out (12f)	

Yingtian kehai optic component co., ltd. Address: Yingtian City Industrial Park ,Jiangxi P.R.C

Post cord:335000 TeL: +086-0701-6317506 Fax: +086-0701-6317508

http://www.kh-optic.com E-mail: ytqff@163.com